SPRING WATER BOTTLING PLANT

LJESKOVAC

WATER SOURCE MAREZA - CAPITAL CITY PODGORICA



INTRODUCTION

PE Water & Sewerage Podgorica intention is to construct spring water plant on watersource Mareza near Capital city of Podgorica. Location of the future factory is situated in the first protection zone of watersource Mareza. Public enterprise provides all necessary infrastructure and try to provide concession for drinkable water capacity of 15 l/sec. Intention of PE Water & Sewerage Podgorica is to find partner on this matter.



COMMUNICATION

Land with complete infrastructure for the factory building is situated nearby Capital city of Podgorica, 9 kilometers away. Location is completely connected with modern roads, with network of regional roads; railway Beograd-Bar is 10 kilometers away from watersource while Bar port is 60 kilometers away from there.

SPRING AND FACTORY LOCATION

Spring zone Mareza is of the lenght of about 1000 meters. Watersource capacity is in the range from 1.8-10 m3/sec. This watersource is characterized by high number of sources where bigger sources are capped, while huge number of littlle sources flows free in operation zone. Zone Ljeskovac is situated in absolute elevation of 32,68 (mnm). Water analyses which were done in the past 10 years show an outstanding quality with favour composition of minerals having temperature of 9-11°C.

Factory location is provided within the protected zone of Mareza source on flat ground with peaks about 33 mnm, next to an asphalt road.

From water intake water will be able to go through the pipeline to the location of spring water bottling plant.

Water supply is on the flat fields at the distance of about 800 meters. Position of the factory is provided next to asphalt road which would facilitate transport of the factory products.

Position of future factory does not make negative effects and does not provide development of a further catchment requested amounts of water on watersource Mareza. Amount of water which would be bottled is approximately 60-150 l/sec which presents insignificant amuont when reffering to minimum capacity of watersource Mareza.



FINANCIAL MODEL

This project has full support of local authority. Proposed financial model is public-private partnership (PPP):

- Proposed portion of PE Water & Sewerage Podgorica will be land–location for the factory with necessery infrastructure and concession for water use.
- Portion of partner will be construction of the factory for water bottling.
- Percentage of ownership will be determined by the investment share between both sides.

WATER QUALITY TESTING RESULTS

PERIOD 2006-2007

Water quality was tested by Institute for Public health of Montenegro and CETI (Center for Ecotochsic investigation)

Parameter	minimum value	maximum value	Maximum permissible value of drinking water	Maximum permissible value of bottled water (Official gazzete Montenegro 42/98)	Maximum permissible value of bottled water (Official gazzete Montenegro 53/05)
${}^{T}_{water,}$	10	10,1	-	-	-
$T_{air,}$ ⁰ C	11,5	21,5	-	-	-
turbidity, NTU	0,24	0,28	1	<0,6	-
pH	7,4	7,6	6,8-8,5	6,8-8,5	6,5-9,5
conductivity, μS/cm	242	252	1000	<500	2500
alkalinity	130	140	-	-	-
Suspended matter, mg/l	1	2	without	without	-
Dry residual, mg/l	123	132	-	<500	-
Oxygen saturation %	123	124	-	-	-
Consumption of KMnO ₄ , mg/l	2,8	4,7	<8	<5	-
$COD mg O_2/l$	0,57	0,96	-	<1	<5

Phisical-chemical properties of analysed water

Parameter (mg/l)	minimum value	maximum value	MAC of drinking water	MAC of bottled water (Official gazzete SRJ 42/98)	MAC (Official gazzete SCG 53/05)
chloride	1,98	2,27	200	25	250
sulphate	1,0	2,4	250	25	250
Phosphate	0,01	0,01	-	0,03	-
Nitrate	0,25	0,67	50	5	0,05
Nitrite	< 0.001	<0.001	0,03	without	0,0001
ammonium	<0,05	0,01	0,1	0,01	0,5
silicate	1	1,87	-	-	-
fluoride	0,035	0,04	1,2	1,0	1,5
cyanide	<0,005	<0,005	0,05	without	0,05
Calcium	42,72	44,78	200	100	-
Magnesium	6,10	6,56	50	30	-
HCO ₃ ⁻	158,6	170,8	-	-	-
hardness	7,3	7,7	-	-	-
iron	0,01	0,01	0,3	0,05	0,2
aluminium	<0,02	<0,02	0,2	0,05	0,2
copper	0,001	0,023	2	0,1	0,002
sodium	0,8	1,15	150	20	200
potassium	0,14	0,29	12	10	-
nicl	0,004	0,004	0,02	0,01	0,02
Lead	<0,005	<0,005	0,01	0,05	0,01
mercury	<0,0005	<0,0005	0,001	0,001	0,001
Total chromium	<0,01	<0,01	0,05	0,05	0,05
manganese	0,001	0,002	0,05	0,02	0,05
cadmium	<0,001	<0,001	0,003	0,005	0,003
zinc	0,002	0,003	3	0,1	-
arsen	<0,01	<0,01	0,01	0,05	0,01
phenol	Without (< 0.0005)	Without (< 0.0005)	0,001	without	-
tenzide	Without	Without	0,1	without	-
	(\0.03)	(0.03)	0.0002	without	0.1
	<0.0001	<0.0001	0,0002	without	0,1
rUDS Total fat and	<0.001	NU,UUU1	0,0003	without	-
oil	<0,001	<0,001	0,1	without	-
mineral oil	<0,001	<0,001	0,01	without	-
pesticide	<0,00001	<0,00001	0,01-0,5	without	0,0005

Composition of chemical elements of analysed water

Results of microbiological analysis of water samples

Parameters	obtained values	MAC (drinking water)	MAC (bottled water)
Total number of	0	100	0
Coliforme bacteria			
Total number of aerobic	1	300	10^*
bacteria			
Fecal coliform	0	0	0
Enterococcus sp.	0	0	0
Proteus spp.	0	0	0
Sulphit.reduct.	0	10	0
Clostridium			
Pseudomonas aeruginosa	0	0	0

*In bottled natural water that has been in circulation for more than 12 hours after filling alolowes aerobic bacteria to 50

Results	of rac	liologic	al anal	ysis	of	water	samp	les

Radionuclide	Obtained values (mBq/l)
²²⁶ Ra (mBq/l)	<16,7
232 Th(mBq/l)	<38,24
40 K(mBq/l)	<35,86
137 Cs(mBq/l)	<10,01

Official gazzete 42/98 Regulation of sanitary drinking water quality Official gazzete 53/05 Regulatino of quality and other requirements for natural mineral water, natural spring water and water having low contents of minerals